

## DELIVERY CAPACITIES

MODELS: 80VP, 125VP, 170VP



### WARNING

LP & NG ARE EXTREMELY FLAMMABLE SO  
TAKE EXTRA PRECAUTIONS WHEN  
PERFORMING ANY WORK TO THE HEATER

#### QUICK REFERENCE FOR MEASURING WATER FLOW RATE

| <u>GPM</u> | <u>QUART JAR</u><br>(in seconds) | <u>GALLON JUG</u><br>(in seconds) |
|------------|----------------------------------|-----------------------------------|
| .50        | 30                               | 120                               |
| .75        | 20                               | 80                                |
| 1.00       | 15                               | 60                                |
| 1.25       | 12                               | 48                                |
| 1.50       | 10                               | 40                                |
| 1.75       | 8.50                             | 34                                |
| 2.00       | 7.50                             | 30                                |
| 2.25       | 6.75                             | 27                                |
| 2.50       | 6.00                             | 24                                |
| 2.75       | 5.50                             | 22                                |
| 3.00       | 5.00                             | 20                                |
| 3.25       | 4.50                             | 18                                |
| 3.50       | 4.25                             | 17                                |
| 3.75       | 4.00                             | 16                                |
| 4.00       | 3.75                             | 15                                |

#### MINIMUM ACTIVATION FLOW RATES REQUIRED PER MODEL

|                            |         |
|----------------------------|---------|
| MODEL 38B                  | .50 GPM |
| MODEL 125B / 125BS         | .50 GPM |
| MODEL 125X / 125FX / 125HX | .50 GPM |
| MODEL 240FX                | .75 GPM |
| MODEL 80VP                 | .75 GPM |
| MODEL 125VP                | .75 GPM |
| MODEL 170                  | 1.1 GPM |
| MODEL 125BL                | 1.8 GPM |
| MODEL 170P+ BOOSTER        | 3 GPM   |
| MODEL 170 I RECIRC         | 4 GPM   |